

parametric information schema



Table of Contents

1.- Introduction. 2

2.- Database structure. 3

3.- Database relations. 12

4.- Database attributes. 19

1.- Introduction :

This paper is about the design of the NCEDC schema for the parametric information. This schema was designed to be able to store all the information from the CNSS format, following as much as possible the CSS 3.0 schema.

There are 15 relations in the schema. The information stored in these relations includes:

- Event information, including preferred origin, preferred magnitude, etc.
- Multiple origins for an event.
- Multiple magnitudes for each origin.
- Arrivals (seismic signals).
- Association of arrivals with origins.
- Association of amplitudes with origins, as well as with magnitudes.
- Moment tensor information.
- Association of coda information with magnitudes.
- Association of coda information with origins.
- Information about last values used for keys.

The remainder of this volume consists of three chapters:

Chapter 2	*Database structure* Each relation is defined.
Chapter 3	*Database relations* The logical design of the database is expressed in an Entity-Relationship diagram and each relation is described to identify the key fields and the links among the relations.
Chapter 4	*Database attributes* Each attribute is described.

2.- Database structure :

This chapter defines the physical structure of each table, as it exists within the DBMS data dictionary. The name of the relation appears in **bold** print at the top left and a description of the table at the top right. **Bold** attributes represent primary keys, *italic* attributes represent foreign keys, and underlined attributes stand for CSS attributes.

Event		Summary information of an event
Attribute	***Type***	***Description***
evid	int	Event identifier
prefor	int	Preferred origin
prefmag	int	Preferred magnitude
prefmec	int	Preferred mechanism
commid	int	Comment identifier
auth	char(15)	Source/originator
subsource	char(8)	Subsystem source
totalarr	int	Total number of arrivals
totalamp	int	Total number of amplitude readings
etype	char(7)	Event type
lddate	int	Load date

Significant_Event		Summary information of a significant event
Attribute	***Type***	***Description***
evid	int	Event identifier
evname	char(80)	Event name
remarks	char(2)	Event indications (felt, damage, ...)
nfelt	int	Number of felt reports
mmi	int	Maximum MM intensity
pga	float	Peak acceleration
lddate	int	Load date

Origin		Data on event location
Attribute	***Type***	***Description***
orid	int	Origin identifier
evid	int	Event identifier
prefmag	int	Preferred magnitude
prefmec	int	Preferred mechanism
commid	int	Comment identifier
date	int	Origin date
lat	float	Estimated latitude
lon	float	Estimated longitude
depth	float	Estimated depth

type	char(2)	Type of location
algorithm	char(15)	Location algorithm used
auth	char(15)	Source/originator
subsource	char(8)	Subsystem source
datumhor	char(8)	Datum type for latitude & longitude
datumver	char(8)	Datum type for vertical
gap	float	Maximum azimuthal gap of stations
distance	float	Distance to nearest station
sdobs	float	Standard error of observations
stime	float	Origin time error
erhor	float	Horizontal error
sdepth	float	Depth error
erlat	float	Error in latitude
erlon	float	Error in longitude
ndef	int	Number of locating phases
nbs	int	Number of S readings
nbp	int	Number of P first motions
sxx	float	Covariance matrix element
syy	float	Covariance matrix element
szz	float	Covariance matrix element
stt	float	Covariance matrix element
sxy	float	Covariance matrix element
sxz	float	Covariance matrix element
syz	float	Covariance matrix element
stx	float	Covariance matrix element
sty	float	Covariance matrix element
stz	float	Covariance matrix element
azismall	float	Azimuth of smallest principal error
dipsmall	float	Dip of smallest principal error
magsmall	float	Magnitude of smallest principal error
aziinter	float	Azimuth of intermediate principal error
dipinter	float	Dip of intermediate principal error
maginter	float	Magnitude of intermediate principal error
azilarge	float	Azimuth of largest principal error
diplarge	float	Dip of largest principal error
maglarge	float	Magnitude of largest principal error
locevid	int	Local event identifier
quality	float	Quality of solution
fdepth	char	Fixed depth
fepi	char	Fixed epicenter
ftime	char	Fixed time
vmodelid	int	Velocity model identifier
cmodelid	int	Crustal model identifier
lddate	int	Load date

Netmag		Summary information on a magnitude
Attribute	***Type***	***Description***
magid	int	Magnitude identifier
orid	int	Origin identifier
evid	int	Event identifier
commid	int	Comment identifier
magnitude	float	Magnitude
magtype	char(6)	Magnitude type
auth	char(15)	Source/originator
subsource	char(8)	Subsystem source
magalgo	char(15)	Magnitude algorithm
nsta	int	Number of stations used
uncertainty	float	Magnitude uncertainty
gap	float	Maximum azimuthal gap of stations
distance	float	Minimum distance of stations
lddate	int	Load date

Arrival		Summary information on a seismic arrival
Attribute	***Type***	***Description***
arid	int	Arrival identifier
evid	int	Event identifier
commid	int	Comment identifier
date	int	Pick date
sta	char(6)	Station code
net	char(8)	Network identifier
iphase	char(8)	Reported phase
auth	char(15)	Source/originator
subsource	char(8)	Subsystem source
channel	char(3)	Channel name
channelsrc	char(8)	Domain of channel name
seedchan	char(3)	SEED channel name
qual	char(1)	Signal onset quality
fm	char(2)	First motion
ema	float	Emergence angle
azimuth	float	Observed azimuth
slow	float	Observed slowness
deltim	float	Delta time
delinc	float	Error in angle
delaz	float	Delta azimuth
delslo	float	Delta slowness
quality	float	Quality
snr	float	Signal to noise ratio
lddate	int	Load date

AssocArO		Data associating arrivals with origins
Attribute	***Type***	***Description***
orid	int	Origin identifier
arid	int	Arrival identifier
commid	int	Comment identifier
iphase	char(8)	Associated phase
importance	float	Importance of phase
delta	float	Station to event distance
seaz	float	Station to event azimuth
wgt	float	Location weight
timeres	float	Time residual
azres	float	Azimuth residual
emares	float	Incidence angle residual
slores	float	Slowness residual
vmodelid	int	Velocity model identifier
scorr	float	Station correction in seconds
sdelay	float	Station delay
lddate	int	Load date

Amp	Summary information on an amplitude reading	
Attribute	***Type***	***Description***
ampid	int	Amplitude identifier
evid	int	Event identifier
commid	int	Comment identifier
date	int	Amplitude date
sta	char(6)	Station code
net	char(8)	Network identifier
iphase	char(8)	Reported phase
amplitude	float	Amplitude
auth	char(15)	Source/originator
subsource	char(8)	Subsystem source
channel	char(3)	Channel name
channelsrc	char(8)	Source of channel name
seedchan	char(3)	SEED channel name
amptype	char(3)	Amplitude type
units	char(4)	Units of amplitude
ampmeas	char(1)	Amplitude measure
eramp	float	Error in amplitude
flagamp	char(4)	Flag to indicate whether amplitude is over P packet,S packet,entire waveform.
per	float	Period
snr	float	Signal to noise ratio
tau	float	Coda duration (F-P time)
durtype	char(3)	Duration type
lddate	int	Load date

AssocAmO	Data associating amplitudes with origins	
Attribute	***Type***	***Description***
orid	int	Origin identifier
ampid	int	Amplitude identifier
commid	int	Comment identifier
delta	float	Station to event distance
seaz	float	Station to event azimuth
importance	float	Importance of amplitude
lddate	int	Load date

AssocAmM		Data associating amplitudes with magnitudes
Attribute	***Type***	***Description***
magid	int	Magnitude identifier
ampid	int	Amplitude identifier
commid	int	Comment identifier
weight	float	Weight code
mag	float	Magnitude for this station reading
magres	float	Magnitude residual
magcorr	float	Magnitude correction for this station
lddate	int	Load date

Remark		Comments
Attribute	***Type***	***Description***
commid	int	Comment identifier
lineno	int	Comment line number
remark	char(80)	Free format comment
lddate	int	Load date

Lastid		Counter values (Last value used for keys)
Attribute	***Type***	***Description***
keyname	char(15)	Identifier name (arid, orid, etc.)
keyvalue	int	Last value used for that identifier
lddate	int	Load date

Mec		Summary information on a moment tensor
Attribute	***Type***	***Description***
mecid	int	Mechanism identifier
oridin	int	Origin identifier (input)
oridout	int	Origin identifier (output)
evid	int	Event identifier
magid	int	Mw magnitude identifier
commid	int	Comment identifier
mechtype	char(2)	Mechanism/moment type
mecalgo	char(15)	Mechanism algorithm
scalar	float	Scalar moment
erscalar	float	Error in scalar moment
tft	char(8)	Time function type
tfd	float	Time function duration
exp	int	Exponent of moment tensor elements
mxx	float	m_xx

myy	float	m_yy
mzz	float	m_zz
mxy	float	m_xy
mxz	float	m_xz
myz	float	m_yz
unmxx	float	Uncertainty in m_xx
unmyy	float	Uncertainty in m_yy
unmzz	float	Uncertainty in m_zz
unmxy	float	Uncertainty in m_xy
unmxz	float	Uncertainty in m_xz
unmyz	float	Uncertainty in m_yz
srcduration	float	Source half-duration
auth	char(15)	Source/origin
subsource	char(8)	Subsystem source
strike1	int	Strike 1 of best double couple
dip1	int	Dip 1 of best double couple
rake1	int	Rake 1 of best double couple
strike2	int	Strike 2 of best double couple
dip2	int	Dip 2 of best double couple
rake2	int	Rake 2 of best double couple
unstrike1	float	Uncertainty in strike 1
undip1	float	Uncertainty in dip 1
unrake1	float	Uncertainty in rake 1
unstrike2	float	Uncertainty in strike 2
undip2	float	Uncertainty in dip 2
unrake2	float	Uncertainty in rake 2
eigenp	float	Eigen pressure
plungep	int	Plunge pressure
strikep	int	Strike pressure
eigenn	float	Eigen null
plungen	int	Plunge null
striken	int	Strike null
eigent	float	Eigen tension
plunget	int	Plunge tension
striket	int	Strike tension
nsta	int	Number of stations used in solution
pvr	int	Percent variance reduction
quality	float	Quality
pdc	int	Percent double couple
pclvd	int	Percent compensated linear vector dipole
piso	int	Percent isotropic
date	int	Date solution created
lddate	int	Load date

Coda		Summary information on a coda
Attribute	***Type***	***Description***
coid	int	Coda identifier
evid	int	Event identifier
commid	int	Comment identifier
sta	char(6)	Station code
net	char(8)	Network code
auth	char(15)	Source/originator
subsource	char(8)	Subsystem source
channel	char(3)	Channel name
channelsrc	char(8)	Source of channel name
seedchan	char(3)	SEED channel name
codatype	char(3)	Coda type
afix	float	Nominal coda amplitude
afree	float	Free amplitude
qfix	float	Fixed coda decay constant
qfree	float	Free decay
tau	float	Coda duration (F-P time)
nsample	int	Number of code sample windows
rms	float	Residual of mean squares for coda fit
durtype	char(3)	Duration type
iphase	char(8)	Reported phase
eramp	float	Error in amplitude
units	char(4)	Units of amplitude
time1	int	Time for pair 1
amp1	int	Amplitude for pair 1
time2	int	Time for pair 2
amp2	int	Amplitude for pair 2
time3	int	Time for pair 3
amp3	int	Amplitude for pair 3
time4	int	Time for pair 4
amp4	int	Amplitude for pair 4
time5	int	Time for pair 5
amp5	int	Amplitude for pair 5
time6	int	Time for pair 6
amp6	int	Amplitude for pair 6
lddate	int	Load date

AssocCoM		Data associating codas with magnitudes
Attribute	***Type***	***Description***
magid	int	Magnitude identifier
coid	int	Coda identifier
commid	int	Comment identifier
lddate	int	Load date

AssocCoO		Data associating codas with origins
Attribute	***Type***	***Description***
orid	int	Origin identifier
coid	int	Coda identifier
commid	int	Comment identifier
lddate	int	Load date

3.- Database relations :



This chapter describes the DBMS relations that comprise the version 1.4 schema. The information given here, along with that in Chapter 4, *Database attributes*, constitutes the data dictionary. There's an entry for each relation. Within the entry, the relation's name appears first, followed by a list of its attributes. A brief description completes the entry.

Keys provide the link by which tables are joined. The following definitions explain the several types of keys.

- A primary key (which can be a concatenation of several attributes) uniquely identifies a row in the table. For example, each **Origin** record is unique by *lat, lon, depth,* and *time*.
- An alternate key also uniquely identifies a row in the table and may be used as the primary key. For example, *orid* may also be used as the primary key for the **Origin** table.
- A foreign key is another table's primary key. Thus, *evid* is a foreign key in the **Origin** table, but is the primary key in the **Event** table. Similarly, *commid* is a foreign key in many of the tables and the primary key in **Remark**.

Name:	**Event**
Keys:	
	Primary: *evid*
	Foreign: *prefor, prefmag, prefmec, commid*
Data:	*auth, subsource, totalarr, totalamp, etype, lddate*
Description:	Event to origin connection. The purpose of this relation is to allow the connection of multiple origins to one event. *prefor* points to the preferred origin. *prefmag* points to the preferred magnitude. *prefmec* points to the preferred mechanism.

Name:	**Significant_Event**
Keys:	
	Primary: *evid*
Data:	*evname, remarks, nfelt, mmi, pga, lddate*
Description:	This relation stores information about significant events.

Name:	**Origin**
Keys:	
	Primary: *orid* Foreign: *evid, prefmag, prefmec, commid*
Data:	*date, lat, lon depth, type, algorithm, auth, subsource, datumhor, datumver, gap, distance, sdobs, stime, erhor, sdepth, erlat, erlon, ndef, nbs, nbp, sxx, syy, szz, stt, sxy, sxz, syz, stx, sty, stz, azismall, dipsmall, magsmall, aziinter, dipinter, maginter, azilarge, diplarge, maglarge, locevid, quality, fdepth, fepi, ftime, vmodelid, cmodelid, lddate*
Description:	Summary of hypocentral parameters. Information describing a derived or reported origin for a particular event is stored in this table.

Name:	**Netmag**
Keys:	
	Primary: *magid* Foreign: *orid, evid, commid*
Data:	*magnitude, magtype, auth, subsource, magalgo, nsta, uncertainty, gap, distance, lddate*
Description:	This table summarizes estimates of magnitudes of different types for an event. Each magnitude has a unique *magid*.

Name:	**Arrival**
Keys:	
	Primary: *arid* Foreign: *evid, commid*
Data:	*date, sta, net, iphase, auth, subsource, channel, channelsrc, seedchan, qual, fm, ema, azimuth, slow, deltim, delinc, delaz, delslo, quality, snr, lddate*
Description:	Summary information on a seismic arrival. Information characterizing a "seismic phase" observed at a particular station is saved here.

Name:	**AssocArO**
Keys:	
	Primary: *orid, arid* Foreign: *commid*
Data:	*iphase, importance, delta, seaz, wgt, timeres, azres, emares, slores, vmodelid, scorr, sdelay, lddate*
Description:	Data associating arrivals with origins. This table has information that connects arrivals (i.e., entries in the **Arrival** relation) to a particular origin. It has a composite key made of *arid* and *orid*.

Name:	**Amp**
Keys:	
	Primary: *ampid* Foreign: *evid, commid*
Data:	*date, sta, net, iphase, amplitude, auth, subsource, channel, channelsrc, seedchan, amptype, units, ampmeas, eramp, flagamp, per, snr, tau, durtype, lddate*
Description:	This table contains information about amplitude readings.

Name:	**AssocAmO**
Keys:	
	Primary: *orid, ampid* Foreign: *commid*
Data:	*delta, seaz, importance, lddate*
Description:	Data associating amplitudes with origins. This table has information that connects amplitudes (i.e., entries in the **Amp** relation) to a particular origin. It has a composite key made of *ampid* and *orid*.

Name:	**AssocAmM**
Keys:	
	Primary: *magid, ampid* Foreign: *commid*
Data:	*weight, mag, magres, magcorr, lddate*
Description:	Data associating amplitudes with magnitudes. This table has information that connects amplitudes (i.e., entries in the **Amp** relation) to a particular magnitude. It has a composite key made of *magid* and *ampid*.

Name:	**Remark**
Keys:	
	Primary: *commid*, *lineno*
Data:	*remark, lddate*
Description:	Comments. This relation may be used to store free-form comments that embellish records of other relations. The *commid* field in many relations refers to a tuple in the **Remark** table.

Name:	**Lastid**
Keys:	
	Primary: *keyname*
Data:	*keyvalue*, *lddate*
Description:	Counter values (last value used for keys). This relation is a reference table from which programs may retrieve the last sequential value of one of the numeric keys. Unique keys are required before inserting a record in numerous tables. The table has exactly one row for each *keyname*.

Name:	**Mec**
Keys:	
	Primary: *mecid* Foreign: *evid, magid, commid*
Data:	*oridin, oridout, mechtype, mecalgo, scalar, erscalar, tft, tfd, exp, mxx, myy, mzz, mxy, mxz, myz, unmxx, unmyy, unmzz, unmxy, unmxz, unmyz, srcduration, auth, subsource, strike1, dip1, rake1, strike2, dip2, rake2, unstrike1, undip1, unrake1, unstrike2, undip2, unrake2, eigenp, plungep, strikep, eigenn, plungen, striken, eigent, plunget, striket, nsta, pvr, quality, pdc, pclvd, piso, date, lddate*
Description:	Mechanisms. This relation is used to store information about moment tensors.

Name:	**Coda**
Keys:	
	Primary: *coid* Foreign: *evid, commid*
Data:	*sta, net, auth, subsource, channel, channelsrc, seedchan, codatype, afix, afree, qfix, qfree, tau, nsample, rms, durtype, iphase, eramp, units, time1, amp1, time2, amp2, time3, amp3, time4, amp4, time5, amp5, time6, amp6, lddate*
Description:	This relation is used to store information about codas.

Name:	**AssocCoM**
Keys:	
	Primary: *magid, coid* Foreign: *commid*
Data:	*lddate*
Description:	Data associating codas with magnitudes. This table has information that connects codas (i.e., entries in the **Coda** relation) to a particular magnitude. It has a composite key made of *magid* and *coid*.

Name:	**AssocCoO**
Keys:	
	Primary: *orid, coid* Foreign: *commid*
Data:	*lddate*
Description:	Data associating codas with origins. This table has information that connects codas (i.e., entries in the **Coda** relation) to a particular origin. It has a composite key made of *orid* and *coid*.

4.- Database attributes :

This chapter describes each of the attributes used in the version 1.4 schema. Descriptions of the relations are found in Chapter 3, *Database relations*.

Name:	*afix*
Relations:	**Coda**
Description:	Nominal coda amplitude.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*afix* > 0.0

Name:	*afree*
Relations:	**Coda**
Description:	Free amplitude.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*afree* > 0.0

Name:	*algorithm*
Relations:	**Origin**
Description:	Location algorithm used. This is a brief textual description of the algorithm used for computing a seismic origin.
Datatype:	***char(15)***
NULL Value:	***Yes***
Range:	Any free-format string up to 15 characters

Name:	*ampid*
Relations:	**Amp**, **AssocAmO**, **AssocAmM**
Description:	Amplitude identification. Each amplitude is assigned a unique positive integer identifying it. This number is used in the **AssocAmO** relation along with the origin identifier to link **Amp** and **Origin**. This number is used also in the **AssocAmM** relation along with the magnitude identifier to link **Amp** and **Netmag**.
Datatype:	***int***
NULL Value:	***No***
Range:	*ampid* > 0

Name:	*amplitude*
Relations:	**Amp**
Description:	Amplitude in appropriate units for type.
Datatype:	***float***
NULL Value:	***No***
Range:	*amplitude* > 0.0

Name:	*ampmeas*
Relations:	**Amp**
Description:	Amplitude measure.
Datatype:	***char(1)***
NULL Value:	***Yes***
Range:	*ampmeas* ∈ {0 | 1} 0 = peak-to-peak 1 = zero-to-peak

Name:	*amptype*
Relations:	**Amp**
Description:	Amplitude type.
Datatype:	***char(3)***
NULL Value:	***Yes***
Range:	*amptype* ∈ {C | WA | WAS | PGA | PGV | PGD} C = coda WA = Wood-Anderson photographic WAS = Wood-Anderson synthetic PGA = peak ground acceleration PGV = peak ground velocity PGD = peak ground displacement

Name:	*amp1, amp2, amp3, amp4, amp5, amp6*
Relations:	***Coda***
Description:	Amplitude for pairs.
Datatype:	***int***
NULL Value:	***Yes***
Range:	*amp1, amp2, amp3, amp4, amp5, amp6* > 0

Name:	*arid*
Relations:	**Arrival**, **AssocArO**
Description:	Arrival identifier. Each arrival is assigned a unique positive integer identifying it. This number is used in the **AssocArO** relation along with the origin identifier to link **Arrival** and **Origin**.
Datatype:	***int***
NULL Value:	***No***
Range:	*arid* > 0

Name:	*auth*
Relations:	**Event**, **Origin**, **Netmag**, **Arrival**, **Amp**, **Mec**, **Coda**
Description:	The *auth* field specifies the source of the information. This may be a network identifier (FDSN or otherwise), or any other string indicating the source of the information in the record.
Datatype:	***char(15)***
NULL Value:	***No***
Range:	Any free-format string up to 15 characters

Name:	*aziinter*
Relations:	**Origin**
Description:	Azimuth of intermediate principal error.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$0.0 \leq aziinter \leq 360.0$
Units:	***Degrees***

Name:	*azilarge*
Relations:	**Origin**
Description:	Azimuth of largest principal error.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$0.0 \leq azilarge \leq 360.0$
Units:	***Degrees***

Name:	*azimuth*
Relations:	**Arrival**
Description:	Observed azimuth. This is the estimated station-to-event azimuth measured clockwise from north.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$0.0 \leq azimuth \leq 360.0$
Units:	***Degrees***

Name:	*azismall*
Relations:	**Origin**
Description:	Azimuth of smallest principal error.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$0.0 \leq azismall \leq 360.0$
Units:	***Degrees***

Name:	*azres*
Relations:	**AssocArO**
Description:	Azimuth residual. This is the difference between the measured station-to-event azimuth for an arrival and the true azimuth. The "true" azimuth is the bearing to the inferred event origin.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$-180.0 \leq azres \leq 180.0$
Units:	***Degrees***

Name:	*channel*
Relations:	**Arrival**, **Amp**, **Coda**
Description:	Channel name.
Datatype:	***char(3)***
NULL Value:	***Yes***
Range:	Any valid channel name, which may be network-specific. Networks using SEED channel names should use the same value for *channel* and *seedchan*

Name:	*channelsrc*
Relations:	**Arrival**, **Amp**, **Coda**
Description:	Domain for channel. This specifies what naming convention is used for the channel name (i.e. SEED, USGS, etc.).
Datatype:	***char(8)***
NULL Value:	***Yes***
Range:	Any free-format string up to 8 characters long

Name:	*cmodelid*
Relations:	**Origin**
Description:	Crustal model identifier.
Datatype:	***int***
NULL Value:	***Yes***
Range:	*cmodelid* > 0

Name:	*codatype*
Relations:	**Coda**
Description:	Coda type.
Datatype:	***char(3)***
NULL Value:	***Yes***
Range:	*codatype* ∈ {P | S} P = USGS P-wave coda S = UCB S-wave coda

Name:	*coid*
Relations:	**Coda**, **AssocCoM**, **AssocCoO**
Description:	Coda identification. Each coda is assigned a unique positive integer which identifies it in the database.
Datatype:	***int***
NULL Value:	***No***
Range:	*coid* > 0

Name:	*commid*
Relations:	**Event**, **Origin**, **Netmag**, **Arrival**, **AssocArO**, **Amp**, **AssocAmO**, **AssocAmM**, **Remark**, **Mec**, **Coda**, **AssocCoM**, **AssocCoO**
Description:	Comment identification. This is a key used to point to free-form comments entered in the **Remark** relation. These comments store additional information about a tuple in another relation. Within the **Remark** relation, there may be many tuples with the same *commid* and different *lineno*, but the same *commid* will appear in only one other tuple among the rest of the relations in the database.
Datatype:	***int***
NULL Value:	***Yes*** (***No*** in the **Remark** relation)
Range:	*commid* > 0

Name:	*date*
Relations:	**Origin**, **Arrival**, **Amp**, **Mec**
Description:	The date of associated with information in the record, in true epoch format.
Datatype:	***int***
NULL Value:	**No**
Range:	*date* > February 10, 1653
Units:	***Seconds***

Name:	*datumhor*
Relations:	**Origin**
Description:	Datum type for horizontal (latitude and longitude) coordinates.
Datatype:	***char(8)***
NULL Value:	***Yes***
Range:	*datumhor* ∈ { NAD27 | WGS84}

Name:	*datumver*
Relations:	**Origin**
Description:	Datum type for depth or elevation.
Datatype:	***char(8)***
NULL Value:	***Yes***
Range:	*datumver* ∈ { NAD27 | WGS84 | AVERAGE} AVERAGE = average of stations

Name:	*delaz*
Relations:	**Arrival**
Description:	Delta azimuth. This attribute gives the standard deviation of the azimuth of a signal.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*delaz* > 0.0
Units:	***Degrees***

Name:	*delinc*
Relations:	**Arrival**
Description:	Error in angle.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*delinc* ≥ 0.0
Units:	***Degrees***

Name:	*delslo*
Relations:	**Arrival**
Description:	Delta slowness. This attribute gives the standard deviation of the slowness of a signal.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*delslo* > 0.0
Units:	***Seconds/Kilometers***

Name:	*delta*
Relations:	**AssocArO**, **AssocAmO**
Description:	Source-receiver distance. This attribute is the arc length, over the earth's surface, of the path the seismic phase follows from source to receiver. The location of the origin is specified in the origin record referenced by the attribute *orid*. The attribute *arid* points to the record in the **Arrival** relation that identifies the receiver. The value of the attribute can exceed 180 degrees, it can even exceed 360 degrees, the geographic distance between source and receiver is *delta* mod(180).
Datatype:	***float***
NULL Value:	***Yes***
Range:	*delta* ≥ 0.0
Units:	***Degrees***

Name:	*deltim*
Relations:	**Arrival**
Description:	Delta time. This attribute gives the standard deviation of a detection time.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*deltim* ≥ 0.0
Units:	***Seconds***

Name:	*depth*
Relations:	**Origin**
Description:	Source depth. This attribute gives the depth of the event origin. The reference depth of 0 is usually defined as the average elevation of stations used to determine the origin. Positive values are down, negative values are up from the reference point.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-10.0 ≤ *depth* ≤ 1000.0
Units:	***Kilometers***

Name:	*dipinter*
Relations:	**Origin**
Description:	Dip of intermediate principal error.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-90.0 ≤ *dipinter* ≤ 90.0
Units:	***Degrees***

Name:	*diplarge*
Relations:	**Origin**
Description:	Dip of largest principal error.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-90.0 ≤ *diplarge* ≤ 90.0
Units:	***Degrees***

Name:	*dipsmall*
Relations:	**Origin**
Description:	Dip of smallest principal error.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-90.0 ≤ *dipsmall* ≤ 90.0
Units:	***Degrees***

Name:	*dip1*
Relations:	**Mec**
Description:	Dip 1 of best double couple.
Datatype:	***int***
NULL Value:	***Yes***
Range:	-90 ≤ *dip1* ≤ 90
Units:	***Degrees***

Name:	*dip2*
Relations:	**Mec**
Description:	Dip 2 of best double couple.
Datatype:	***int***
NULL Value:	***Yes***
Range:	-90 ≤ *dip2* ≤ 90
Units:	***Degrees***

Name:	*distance*
Relations:	**Origin**, **Netmag**
Description:	Distance to nearest station.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*distance* ≥ 0.0
Units:	***Kilometers***

Name:	*durtype*
Relations:	**Amp**, **Coda**
Description:	Duration type.
Datatype:	***char(3)***
NULL Value:	***Yes***
Range:	*durtype* ∈ {S} S = S-wave

Name:	*eigenn*
Relations:	**Mec**
Description:	Eigen null.
Datatype:	***float***
NULL Value:	***Yes***

Name:	*eigenp*
Relations:	**Mec**
Description:	Eigen pressure.
Datatype:	***float***
NULL Value:	***Yes***

Name:	*eigent*
Relations:	**Mec**
Description:	Eigen tension.
Datatype:	***float***
NULL Value:	***Yes***

Name:	*ema*
Relations:	**Arrival**
Description:	Emergence angle. This attribute is the emergence angle of an arrival, as observed at a three-component station or array. The value increases from the vertical direction towards the horizontal.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$0.0 \leq ema \leq 90.0$
Units:	***Degrees***

Name:	*emares*
Relations:	**AssocArO**
Description:	Emergence angle residual. This attribute is the difference between an observed emergence angle and the theorical prediction for the same phase, assuming an event location as specified by the accompanying *orid*.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-90.0 ≤ *emares* ≤ 90.0
Units:	***Degrees***

Name:	*eramp*
Relations:	**Amp**, **Coda**
Description:	Error in amplitude.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*eramp* ≥ 0.0

Name:	*erhor*
Relations:	**Origin**
Description:	Horizontal error. This attribute denotes the location uncertainty that accompanies the location.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*erhor* ≥ 0.0
Units:	***Kilometers***

Name:	*erlat*
Relations:	**Origin**
Description:	Error in latitude. This is the maximum error of the latitude estimate.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*erlat* ≥ 0.0
Units:	***Kilometers***

Name:	*erlon*
Relations:	**Origin**
Description:	Error in longitude. This is the maximum error of the longitude estimate.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*erlon* ≥ 0.0
Units:	***Kilometers***

Name:	*erscalar*
Relations:	***Mec***
Description:	Error in scalar moment.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*erscalar* ≥ 0.0
Units:	***Dynes centimeters***

Name:	*etype*
Relations:	**Event**
Description:	This attribute is used to identify the type of seismic event, when known.
Datatype:	***char(7)***
NULL Value:	***Yes***
Range:	*etype* ∈ {le | re | ts | qb | nt | uk} le = local event re = regional event ts = teleseism qb = quarry blast nt = nuclear test uk = unknown event

Name:	*evid*
Relations:	**Event**, **Significant_Event**, **Origin**, **Netmag**, **Arrival**, **Amp**, **Mec**, **Coda**
Description:	Event identifier. Each event is assigned a unique integer which identifies it in a database. It is possible for several records in the **Origin** relation to have the same *evid*. This indicates there are several opinions about the location of the event. The *evid* does not have to be identical to the local network's event identifier, which is stored in the **Origin** table. This allows to merge data for a single event from multiple sources without insisting that database *evid* is identical to the source's local event identifier.
Datatype:	***int***
NULL Value:	***No***
Range:	*evid* > 0

Name:	*evname*
Relations:	**Significant_Event**
Description:	Event name. This is a descriptive name for major events.
Datatype:	***char(80)***
NULL Value:	***Yes***
Range:	Any free-format string up to 80 characters

Name:	*exp*
Relations:	**Mec**
Description:	Exponent of moment tensor elements.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq exp \leq 32$

Name:	*fdepth*
Relations:	**Origin**
Description:	This attribute indicates if the depth was fixed or not to compute the solution.
Datatype:	***char(1)***
NULL Value:	***Yes***
Range:	*fdepth* ∈ {y | n} y = fixed depth n = free depth

Name:	*fepi*
Relations:	**Origin**
Description:	This attribute indicates if the epicenter was fixed or not to compute the solution.
Datatype:	***char(1)***
NULL Value:	***Yes***
Range:	*fepi* ∈ {y | n} y = fixed epicenter n = free epicenter

Name:	*flagamp*
Relations:	**Amp**
Description:	This attribute is a flag to indicate whether amplitude is over P packet, S packet, entire waveform, etc.
Datatype:	***char(4)***
NULL Value:	***Yes***
Range:	*flagamp* ∈ {P | S | ALL} P = P packet S = S packet ALL = entire waveform

Name:	*fm*
Relations:	**Arrival**
Description:	First motion. This is a two-character indication of first motion. The first character describes first motion seen on short-period channels and the second holds for long-period instruments. Compression (dilation) on a short-period sensor is denoted by c(d) and compression (dilation) on a long-period sensor is denoted by u(r). Empty character positions will be indicated by dots (e.g., ".r").
Datatype:	***char(2)***
NULL Value:	***Yes***
Range:	All two-letter permutations of (c | d | .} ∪ {u | r | .}

Name:	*ftime*
Relations:	**Origin**
Description:	This attribute indicates if the origin time was fixed or not to compute the solution.
Datatype:	***char(1)***
NULL Value:	***Yes***
Range:	*ftime* ∈ {y | n} y = fixed origin time n = free origin time

Name:	*gap*
Relations:	**Origin**, **Netmag**
Description:	Azimuthal gap.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$0.0 \leq gap \leq 360.0$
Units:	***Degrees***

Name:	*importance*
Relations:	**AssocArO**, **AssocAmO**
Description:	This attribute denotes the importance of a phase or an amplitude for a solution. 0.0 means no importance, 1.0 implies extremely important.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$0.0 < importance \leq 1.0$

Name:	*iphase*
Relations:	**Arrival**, **AssocArO**, **Coda**
Description:	Reported phase. This eight-character field holds the name initially given to a seismic phase. Standard seismological labels for the types of signals (or phases) are used (e.g., P, PKP, PcP, pP). Both upper and lower case letters are available and should be used when appropriate, for example, pP or PcP.
Datatype:	***char(8)***
NULL Value:	***Yes***
Range:	Any free-format string up to 8 characters

Name:	*keyname*
Relations:	**Lastid**
Description:	Identifier type. This attribute contains the actual name of a key whose last assigned numeric value is saved in *keyvalue*.
Datatype:	***char(15)***
NULL Value:	***No***
Range:	Any free-format string up to 15 characters long

Name:	*keyvalue*
Relations:	**Lastid**
Description:	Current identifier value. This attribute maintains the last assigned value (a positive integer) of the counter for the specified *keyname*. The number *keyvalue* is the last counter value used for the attribute *keyname*. Key values are maintained in the database to ensure uniqueness.
Datatype:	***int***
NULL Value:	***No***
Range:	*keyvalue* > 0

Name:	*lat*
Relations:	**Origin**
Description:	Latitude. This attribute is the geographic latitude. Locations north of the equator have positive latitudes.
Datatype:	***float***
NULL Value:	***No***
Range:	$-90.0 \leq lat \leq 90.0$
Units:	***Degrees***

Name:	*lddate*
Relations:	**Event**, **Significant_Event**, **Origin**, **Netmag**, **Arrival**, **AssocArO**, **Amp**, **AssocAmO**, **AssocAmM**, **Remark**, **Lastid**, **Mec**, **Coda**, **AssocCoM**, **AssocCoO**
Description:	Load date. Date and time that the record was created or last modified, in true epoch time.
Datatype:	***int***
NULL Value:	***No***
Range:	*lddate* > February 10, 1653
Units:	***Seconds***

Name:	*lineno*
Relations:	**Remark**
Description:	Comment line number. This integer attribute is assigned as a sequence number for multiple line comments. The combination of *commid* and *lineno* is unique.
Datatype:	***int***
NULL Value:	***No***
Range:	*lineno* > 0

Name:	*locevid*
Relations:	**Origin**
Description:	Local event identifier. This attribute describes the original event identifier of the event. In combination with *auth* and *subsource*, it can be used to uniquely identify the original event identifier from that source. For example, waveforms from the original source may be associated with this identifier.
Datatype:	***int***
NULL Value:	***Yes***
Range:	Any valid integer

Name:	*lon*
Relations:	**Origin**
Description:	Longitude. This attribute is the geographic longitude. Longitudes are measured positive east of the Greenwich meridian.
Datatype:	***float***
NULL Value:	***No***
Range:	$-180.0 \leq lon \leq 180.0$
Units:	***Degrees***

Name:	*mag*
Relations:	**AssocAmM**
Description:	Magnitude for this station reading.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$-10.0 < mag < 10.0$

Name:	*magalgo*
Relations:	**Netmag**
Description:	This attribute represents the algorithm used to compute the magnitude.
Datatype:	***char(15)***
NULL Value:	***Yes***
Range:	Any free-format string up to 15 characters

Name:	*magcorr*
Relations:	**AssocAmM**
Description:	Magnitude correction for this station.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$-10.0 \leq magcorr \leq 10.0$
Units:	***Magnitude units***

Name:	*magid*
Relations:	**Netmag**, **AssocAmM**, **Mec**, **AssocCoM**
Description:	Magnitude identifier. This key is used to identify a magnitude in the **Netmag** relation. It is required for every magnitude.
Datatype:	***int***
NULL Value:	***No***
Range:	$magid > 0$

Name:	*maginter*
Relations:	**Origin**
Description:	Magnitude of intermediate principal error.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$maginter \geq 0.0$
Units:	***Kilometers***

Name:	*maglarge*
Relations:	**Origin**
Description:	Magnitude of largest principal error.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*maglarge* ≥ 0.0
Units:	***Kilometers***

Name:	*magnitude*
Relations:	**Netmag**
Description:	Magnitude. This gives the magnitude value of the type indicated by *magtype*.
Datatype:	***float***
NULL Value:	***No***
Range:	-10.0 < *magnitude* < 10.0

Name:	*magres*
Relations:	**AssocAmM**
Description:	Magnitude residual.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*magres* ≥ 0.0

Name:	*magsmall*
Relations:	**Origin**
Description:	Magnitude of smallest principal error.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*magsmall* ≥ 0.0
Units:	***Kilometers***

Name:	*magtype*
Relations:	**Netmag**
Description:	Magnitude type. This character string is used to specify the type of the magnitude measure.
Datatype:	***char(6)***
NULL Value:	***No***
Range:	*magtype* ∈ {a | b | e | l | l1 | l2 | lg | c | s | w | z | B | un | d | h | n} a = primary amplitude magnitude (Jerry Eaton's XMAG) b = body-wave magnitude e = energy magnitude l = local magnitude l1 = traditional UCB local magnitude l2 = network UCB local magnitude lg = Lg magnitude c = primary coda magnitude s = Ms – surface wave magnitude w = moment magnitude z = low gain (Z component) magnitude of Hirshorn and Lindh (1989) B = magnitude estimated from 14-kg Benioff's un = unknown magnitude type d = duration magnitude h = helicorder magnitude (CIT, short-period Benioff) n = no magnitude

Name:	*mecid*
Relations:	**Mec**
Description:	Mechanism identification. Each mechanism is assigned a unique positive integer which identifies it in the database.
Datatype:	***int***
NULL Value:	***No***
Range:	*mecid* > 0

Name:	*mecalgo*
Relations:	**Mec**
Description:	This attribute represents the algorithm used to compute the mechanism.
Datatype:	***char(15)***
NULL Value:	***Yes***
Range:	Any free-format string up to 15 characters

Name:	*mechtype*
Relations:	**Mec**
Description:	Mechanism/moment type.
Datatype:	***char(2)***
NULL Value:	***Yes***
Range:	*mechtype* ∈ {C | C0 | F | F0 | H | N | S | S0} C = complete-waveform inversion C0 = Dreger's waveform inversion F = first motion mechanism F0 = fpfit H = half duration of S-wave N = near-field inversion S = surface-wave inversion S0 = Romanowicz & Pasyanos surface-wave inversion

Name:	*mmi*
Relations:	**Significant_Event**
Description:	Reported or inferred Mercali intensity for event.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$1 \leq mmi \leq 12$

Name:	*mxx, myy, mzz, mxy, mxz, myz*
Relations:	**Mec**
Description:	Moment tensor elements.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-10.0 < *mxx, myy, mzz, mxy, mxz, myz* < 10.0
Units:	***Dynes centimeters***

Name:	*nbp*
Relations:	**Origin**
Description:	Number of P first motions.
Datatype:	***int***
NULL Value:	***Yes***
Range:	*nbp* ≥ 0

Name:	*nbs*
Relations:	**Origin**
Description:	Number of S phase readings.
Datatype:	***int***
NULL Value:	***Yes***
Range:	*nbs* ≥ 0

Name:	*ndef*
Relations:	**Origin**
Description:	Number of time-defining phases. This attribute is the number of arrivals used to locate an event.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$ndef \geq 0$

Name:	*net*
Relations:	**Arrival**, **Amp**, **Coda**
Description:	Unique network identifier. This character string is the name of a seismic network.
Datatype:	***char(8)***
NULL Value:	***Yes***
Range:	Any free-format string up to 8 characters. If available, use the two character FDSN code for the network

Name:	*nfelt*
Relations:	**Significant_Event**
Description:	Number of felt reports.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$nfelt > 0$

Name:	*nsample*
Relations:	**Coda**
Description:	Number of coda sample windows.
Datatype:	***int***
NULL Value:	***Yes***
Range:	*nsample* > 0

Name:	*nsta*
Relations:	**Netmag**, **Mec**
Description:	Number of stations. This quantity is the number of stations used to compute the magnitude or the mechanism of the event.
Datatype:	***int***
NULL Value:	***Yes***
Range:	*nsta* > 0

Name:	*orid*
Relations:	**Origin**, **Netmag**, **AssocArO**, **AssocAmO**, **AssocCoO**
Description:	Origin identification. Each origin is assigned a unique positive integer which identifies it in the database. The *orid* is used to identify one of the many hypotheses of the actual location of the event.
Datatype:	***int***
NULL Value:	***No***
Range:	*orid* > 0

Name:	*oridin*
Relations:	**Mec**
Description:	Input origin. This attribute holds the origin identifier, *orid*, that points to the origin from which the mechanism was computed.
Datatype:	***int***
NULL Value:	***Yes***
Range:	*oridin > 0*

Name:	*oridout*
Relations:	**Mec**
Description:	Output origin. This attribute holds the origin identifier, *orid*, that points to the origin computed from the mechanism.
Datatype:	***int***
NULL Value:	***Yes***
Range:	*oridout > 0*

Name:	*per*
Relations:	**Amp**
Description:	Signal period. This attribute is the period of the signal described by the *amplitude* record.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*per* > 0.0
Units:	***Seconds***

Name:	*pga*
Relations:	**Significant_Event**
Description:	Peak ground acceleration recorded by any station for the event.Represented in g, where 1.0 = 1g.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*pga* > 0.0
Units:	***g***

Name:	*plungen*
Relations:	**Mec**
Description:	Plunge null.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq plungen \leq 90$
Units:	***Degrees***

Name:	*plungep*
Relations:	**Mec**
Description:	Plunge pressure.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq plungep \leq 90$
Units:	***Degrees***

Name:	*plunget*
Relations:	**Mec**
Description:	Plunge tension.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq plunget \leq 90$
Units:	***Degrees***

Name:	*prefmag*
Relations:	**Event**, **Origin**
Description:	Preferred magnitude. This attribute holds the magnitude identifier, *magid*, that points to the preferred magnitude for a seismic event or an origin.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$prefmag > 0$

Name:	*prefmec*
Relations:	**Event**, **Origin**
Description:	Preferred mechanism. This attribute holds the mechanism identifier, *mecid*, that points to the preferred mechanism for a seismic event or an origin.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$prefmec > 0$

Name:	*prefor*
Relations:	**Event**
Description:	Preferred origin. This attribute holds the origin identifier, *orid*, that points to the preferred origin for a seismic event.
Datatype:	***int***
NULL Value:	***Yes*** (only if no origin exists for the event)
Range:	*prefor* > 0

Name:	*pclvd*
Relations:	**Mec**
Description:	Percent compensated linear vector dipole.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq pclvd \leq 100$

Name:	*pdc*
Relations:	**Mec**
Description:	Percent double couple.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq pdc \leq 100$

Name:	*piso*
Relations:	**Mec**
Description:	Percent isotropic.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq piso \leq 100$

Name:	*pvr*
Relations:	**Mec**
Description:	Percent variance reduction.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$0.0 \leq pvr \leq 100.0$

Name:	*qfix*
Relations:	**Coda**
Description:	Fixed coda decay constant.
Datatype:	***float***
NULL Value:	***Yes***
Range:	Any valid float

Name:	*qfree*
Relations:	**Coda**
Description:	Free decay.
Datatype:	***float***
NULL Value:	***Yes***
Range:	Any valid float

Name:	*qual*
Relations:	**Arrival**
Description:	Onset quality. This single-character flag is used to denote the sharpness of the onset of a seismic phase.
Datatype:	***char(1)***
Null Value:	***Yes***
Range:	*qual* ∈ {i | e | w} i = impulsive e = emergent w = weak

Name:	*quality*
Relations:	**Origin**, **Arrival**, **Mec**
Description:	This attribute denotes the quality of an origin, an arrival, or a mechanism. 1.0 = good, 0.0 = bad.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$0.0 \leq quality \leq 1.0$

Name:	*rake1*
Relations:	**Mec**
Description:	Rake 1 of best double couple.
Datatype:	***int***
NULL Value:	***Yes***
Range:	-180 ≤ *rake1* ≤ 180
Units:	***Degrees***

Name:	*rake2*
Relations:	**Mec**
Description:	Rake 2 of best double couple.
Datatype:	***int***
NULL Value:	***Yes***
Range:	-180 ≤ *rake2* ≤ 180
Units:	***Degrees***

Name:	*remark*
Relations:	**Remark**
Description:	Descriptive text. This single line of text is an arbitrary comment about a record in the database. The comment is linked to its "parent" relation only by forward reference from *commid* in the tuple of the relation of interest.
Datatype:	***char(80)***
NULL Value:	***Yes***
Range:	Any free-format string up to 80 characters long

Name:	*remarks*
Relations:	**Significant_Event**
Description:	This attribute is used to give some information about the event, such as felt or damage.
Datatype:	***char(2)***
NULL Value:	***Yes***
Range:	*remarks* ∈ {f | d} f = felt d = damage

Name:	*rms*
Relations:	**Coda**
Description:	Residual of mean squares for coda fit.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*rms* ≥ 0.0

Name:	*scalar*
Relations:	***Mec***
Description:	Scalar moment.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-10.0 < *scalar* < 10.0
Units:	***Dynes centimeters***

Name:	*scorr*
Relations:	**AssocArO**
Description:	Station correction.
Datatype:	***float***
NULL Value:	***Yes***
Range:	Any valid float
Units:	***Seconds***

Name:	*sdelay*
Relations:	**AssocArO**
Description:	Station delay.
Datatype:	***float***
NULL Value:	***Yes***
Range:	Any valid float
Units:	***Seconds***

Name:	*sdepth*
Relations:	**Origin**
Description:	Depth error. This is the maximum error of the depth estimate.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*sdepth* ≥ 0.0
Units:	***Kilometers***

Name:	*sdobs*
Relations:	**Origin**
Description:	Standard error of one observation. This attribute is derived from the discrepancies in the arrival times of the phases used to locate an event. It is defined as the square root of the sum of the squares of the time residuals, divided by the number of degrees of freedom. The latter is the number of defining observations (*ndef* in **Origin**) minus the dimension of the system solved (4 if depth is allowed to be a free variable, 3 if depth is constrained).
Datatype:	***float***
NULL Value:	***Yes***
Range:	*sdobs* > 0.0

Name:	*seaz*
Relations:	**AssocArO**, **AssocAmO**
Description:	Station to event azimuth. This attribute is calculated from the station and event locations. It is measured clockwise from North.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$0.0 \leq seaz \leq 360.0$
Units:	***Degrees***

Name: *seedchan*

Relations: **Arrival**, **Amp**, **Coda**

Description: SEED channel name. The first character denotes the band code, the second holds for the instrument code and the third one represents the component code.

Datatype: ***char(3)***

NULL Value: ***Yes***

Range: *seedchan* ∈ {E | S | H | B | M | L | V | U | R} ∪
{A | B | D | F | G | H | I | K | L | M | P | R | S | V | T | W} ∪
{Z | N | E | A | B | C | T | R | 1 | 2 | 3 | U | V | W}

Band code:

	Sample rate (Hz)	Corner period (sec)
E = extremely short period	≥ 80	< 10
S = short period	≥ 10 to < 80	< 10
H = high broad band	≥ 80	≥ 10
B = broad band	≥ 10 to < 80	≥ 10
M = mid period	> 1 to < 10	
L = long period	~ 1	
V = very long period	~ 0.1	
U = ultra long period	~ 0.01	
R = extremely long period	~ 0.001	

Instrument code:

A = tiltmeter	B = creepmeter
D = pressure	F = magnetometer
G = gravimeter/accelerometer	H = high gain seismometer
I = humidity	K = temperature
L = low gain seismometer	M = mass position seismometer
P = geophone	R = rainfall
S = linear strainmeter	V = volumetric strain
T = tide meter	W = wind

Component code:

N = north-south	E = east-west
T = transverse	R = radial

Z = vertical
A, B, C = triaxial
1, 2, 3 = orthogonal components but non-traditional orientations
U, V, W = optional components

Name:	*slores*
Relations:	**AssocArO**
Description:	Slowness residual. This attribute gives the difference between an observed slowness and a theorical prediction. The prediction is calculated for the related phase and event origin described in the record.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*slores* ≥ 0.0
Units:	***Seconds/kilometer***

Name:	*slow*
Relations:	**Arrival**
Description:	Observed slowness. This is the observed slowness of a wave as it sweeps across an array.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*slow* ≥ 0.0
Units:	***Seconds/kilometer***

Name:	*snr*
Relations:	**Arrival**, **Amp**
Description:	Signal-to-noise ratio. This is an estimate of the signal relative to that of the noise immediately preceding it.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*snr* > 0.0

Name:	*srcduration*
Relations:	**Mec**
Description:	Source half-duration.
Datatype:	***float***
NULL Value:	***Yes***
Range:	0.0 < *srcduration* < 100.0
Units:	***Seconds***

Name:	*sta*
Relations:	**Arrival**, **Amp**, **Coda**
Description:	Station code. This is the common code-name of a seismic observatory. Generally only three or four characters are used.
Datatype:	***char(6)***
NULL Value:	***No***
Range:	Any free-format string up to 6 characters

Name	*stime*
Relations:	**Origin**
Description:	Origin time error. This attribute denotes the time uncertainty that accompanies the location.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*stime* ≥ 0.0
Units:	***Seconds***

Name:	*striken*
Relations:	**Mec**
Description:	Strike null.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq \text{striken} \leq 360$
Units:	***Degrees***

Name:	*strikep*
Relations:	**Mec**
Description:	Strike pressure.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq \text{strikep} \leq 360$
Units:	***Degrees***

Name:	*striket*
Relations:	**Mec**
Description:	Strike tension.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq \text{striket} \leq 360$
Units:	***Degrees***

Name:	*strike1*
Relations:	**Mec**
Description:	Strike 1 of best double couple.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq strike1 \leq 360$
Units:	***Degrees***

Name:	*strike2*
Relations:	**Mec**
Description:	Strike 2 of best double couple.
Datatype:	***int***
NULL Value:	***Yes***
Range:	$0 \leq strike2 \leq 360$
Units:	***Degrees***

Name:	*stx*, *sty*, *stz*, *sxx*, *sxy*, *sxz*, *syy*, *syz*, *stt*, *szz*
Relations:	**Origin**
Description:	Elements of the covariance matrix for the location defined by *orid*. The covariance matrix is symmetric (and positive definite) so that sxy = syx, etc., (x, y, z, t) refer to latitude, longitude, depth and origin time, respectively. These attributes (together with *sdobs*, *ndef* and *dattype*) provide all the information necessary to construct the K-dimensional (K=2, 3, 4) confidence ellipse or ellipsoids at any confidence limit desired.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*sxx*, *syy*, *szz*, *stt* > 0.0
Units:	*sxx*, *syy*, *szz*, *sxy*, *sxz*, *syz* – ***Kilometers squared*** *stt* – ***Seconds squared*** *stx*, *sty*, *stz* – ***Kilometers/second***

Name:	*subsource*
Relations:	**Event**, **Origin**, **Netmag**, **Arrival**, **Amp**, **Mec**, **Coda**
Description:	A second identifier to specify a unique source within the domain specified by *auth*.
Datatype:	***char(8)***
NULL Value:	***Yes***
Range:	Any free-format string up to 8 characters

Name:	*tau*
Relations:	**Amp**, **Coda**
Description:	Coda duration (F-P time)
Datatype:	***float***
NULL Value:	***Yes***
Range:	*tau* > 0.0
Units:	***Seconds***

Name:	*tfd*
Relations:	***Mec***
Description:	Time function duration.
Datatype:	***float***
Range:	*tfd* > 0.0
Units:	***Seconds***

Name:	*tft*
Relations:	***Mec***
Description:	Time function type.
Datatype:	***char(8)***
Range:	Any free-format string up to 8 characters

Name:	*time1, time2, time3, time4, time5, time6*
Relations:	**Coda**
Description:	Time for pairs.
Datatype:	***int***
NULL Value:	***Yes***
Range:	*time1, time2, time3, time4, time5, time6* > 0
Units:	***Seconds***

Name:	*timeres*
Relations:	**AssocArO**
Description:	Time residual. This attribute is a travel time residual, measured in seconds. The residual is found by taking the observed arrival time (saved in the **Arrival** relation) of a seismic phase and substracting the expected arrival time. The expected arrival time is calculated by a formula based on earth velocity model, an event location and origin time, the distance to the station, and the particular seismic phase.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*timeres* ≥ 0.0
Units:	***Seconds***

Name:	*totalamp*
Relations:	**Event**
Description:	Total number of amplitudes in the database for the specified *evid*. Not all amplitudes have to associated with all (or any) magnitudes or origins.
Datatype:	***int***
NULL Value:	***No***
Range:	*totalamp* ≥ 0

Name:	*totalarr*
Relations:	**Event**
Description:	Total number of arrivals in the database for the specified *evid*. Not all arrivals have to associated with all (or any) origins.
Datatype:	***int***
NULL Value:	***No***
Range:	*totalarr* ≥ 0

Name:	*type*
Relations:	**Origin**
Description:	Type of location.
Datatype:	***char(2)***
NULL Value:	***Yes***
Range:	*type* ∈ {H | C | A} H = hypocenter C = centroid A = amplitude

Name:	*uncertainty*
Relations:	**Netmag**
Description:	Magnitude uncertainty. This is the standard deviation of the accompanying magnitude measurement.
Datatype:	***float***
NULL Value:	***Yes***
Range:	*uncertainty* > 0.0

Name:	*undip1*
Relations:	**Mec**
Description:	Uncertainty in dip 1.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-180.0 ≤ *undip1* ≤ 180.0
Units:	***Degrees***

Name:	*undip2*
Relations:	**Mec**
Description:	Uncertainty in dip 2.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-180.0 ≤ *undip2* ≤ 180.0
Units:	***Degrees***

Name:	*units*
Relations:	**Amp**, **Coda**
Description:	Units of amplitude.
Datatype:	***char(4)***
NULL Value:	***No***
Range:	*units* ∈ {c | s | mm | cm | m | ms | mss | cms | cmss | mms | mmss | mc | nm} c = counts s = seconds mm = millimeters cm = centimeters m = meters ms = meters per second mss = meters per second per second cms = centimeters per second cmss = centimeters per second per second mms = millimeters per second mmss = millimeters per second per second mc = microns nm = nanometers

Name:	*unmxx, unmyy, unmzz, unmxy, unmxz, unmyz*
Relations:	***Mec***
Description:	Uncertainties in moment tensor elements.
Datatype:	***float***
Range:	-10.0 < *unmxx, unmyy, unmzz, unmxy, unmxz, unmyz* < 10.0
Units:	***Dynes centimeters***

Name:	*unrake1*
Relations:	**Mec**
Description:	Uncertainty in rake 1.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-180.0 ≤ *unrake1* ≤ 180.0
Units:	***Degrees***

Name:	*unrake2*
Relations:	**Mec**
Description:	Uncertainty in rake 2.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-180.0 ≤ *unrake2* ≤ 180.0
Units:	***Degrees***

Name:	*unstrike1*
Relations:	**Mec**
Description:	Uncertainty in strike 1.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-180.0 ≤ *unstrike1* ≤ 180.0
Units:	***Degrees***

Name:	*unstrike2*
Relations:	**Mec**
Description:	Uncertainty in strike 2.
Datatype:	***float***
NULL Value:	***Yes***
Range:	-180.0 ≤ *unstrike2* ≤ 180.0
Units:	***Degrees***

Name:	*vmodelid*
Relations:	**Origin**
Description:	Velocity model identification.
Datatype:	***int***
NULL Value:	***Yes***
Range:	*vmodelid* > 0

Name:	*weight*
Relations:	**AssocAmM**
Description:	Weight code.
Datatype:	***float***
NULL Value:	***Yes***
Range:	0.0 < *weight* ≤ 1.0 0.0 = no weight (not used)

Name:	*wgt*
Relations:	**AssocArO**
Description:	Location weight. This attribute gives the final weight assigned to the allied arrival by the location program. It is used primarily for location programs that adaptively weight data by their residuals.
Datatype:	***float***
NULL Value:	***Yes***
Range:	$0.0 \leq wgt < 1.0$

A

afix 19
afree 19
algorithm 19
Amp 7, 15
amp1 21
amp2 21
amp3 21
amp4 21
amp5 21
amp6 21
ampid 20
amplitude 20
ampmeas 20
amptype 21
arid 21
Arrival 5, 14
AssocAmM 8, 16
AssocAmO 7, 15
AssocArO 6, 15
AssocCoM 11, 17
AssocCoO 11, 18
auth 22
aziinter 22
azilarge 22
azimuth 23
azismall 23
azres 23

C

channel 24
channelsrc 24
cmodelid 24
Coda 10, 17
codatype 25
commid 25

D

date 26
datumhor 26
datumver 26
delaz 27
delinc 27
delslo 27
delta 28
deltim 28
depth 29
dip1 30
dip2 30
dipinter 29
diplarge 29
dipsmall 30
distance 31
durtype 31

E

eigenn 31
eigenp 32
eigent 32
ema 32
emares 33
eramp 33
erhor 33
erlat 34
erlon 34
erscalar 34
etype 35
Event 3, 13
evid 35
evname 36
exp 36

F

fdepth 36
fepi 37
flagamp 37
fm. 38
ftime 38

G

gap 39

I

importance 39
iphase 39

K

keyname 40
keyvalue 40

L

Lastid 8, 16
lat. 40
lddate 41
lineno 41
locevid 41
lon 42

M

mag 42
mag*algo* 42
magcorr 43
magid 43
maginter 43
maglarge 44
magnitude 44
magres 44
magsmall 45
magtype 45
Mec 8, 17

mecalgo 46
mechtype 47
mecid 25, 46
mmi 47
mxx 48
mxy 48
mxz 48
myy 48
myz 48
mzz 48

N

nbp 48
nbs 48
ndef 49
net 49
Netmag 5, 14
nfelt 49
nsample 50
nsta 50

O

orid 50
oridin 51
oridout 51
Origin 3, 14

P

pclvd 54
pdc 54
per 51
pga 52
piso 55
plungen 52
plungep 52
plunget 53
prefmag 53
prefmec 53
prefor 54
pvr 55

Q

qfix 55
qfree 56
qual 56
quality 56

R

rake1 57
rake2 57
remark 57
Remark 8, 16
remarks 58
rms 58

S

scalar 58
scorr 59
sdelay 59
sdepth 59
sdobs 60
seaz 60
seedchan 61
Significant_Event 3, 13
slores 62
slow 62
snr 62
srcduration 63
sta 63
stime 63
strike1 65
strike2 65
striken 64
strikep 64
striket 64
stt. 66
stx. 66
sty. 66
stz. 66
subsource 66
sxx 66
sxy 66
sxz 66
syy 66
syz 66
szz. 66

T

tau 67
tfd. 67
tft. 67
time1 68
time2 68
time3 68
time4 68
time5 68
time6 68
timeres 68
totalamp 68
totalarr 69
type 69

U

uncertainty 69
undip1 70
undip2 70
units 71
unmxx 71
unmxy 71
unmxz 71

unmyy 71
unmyz 71
unmzz 71
unrake1 72
unrake2 72
unstrike1 72
unstrike2 73

V

vmodelid 73

W

weight 73
wgt 74